Global alignment Mutr + Muid zerofield Alignment with Millepede

Catherine Silvestre

CEA Saclay

August 25, 2006

Update

Simulations

Reco1

Reco2

Real data

Reco1: aligning run3pp zerofield with survey

Reco2

Update

Simulations

Reco1

Reco2

Real data

Reco1: aligning run3pp zerofield with survey

Reco2

Update

Bugs fixed in the MuID alignment

- output file: writting the correction output files, x corrections were written instead of y and vice versa (alignment/Misalignment.cxx).
- loading corrections: there was a reset missing when loading corrections so that when changing run numbers, corrections were added on top of the previously modified geometry (muigeom/TMuiAlign.h)

Update

Simulations

Reco1

Reco2


Real data

Reco1: aligning run3pp zerofield with survey

110002

Reco1: founding misalignments

MuTr and MuID




Plot description

- The top and bottom plots show w offsets in cm vs each detector (one point per half octant and panel). Middle plot is the number of tracks per detector.
- In blue are the input misalignments; in red the misalignments found by Millepede. The dashed lines separate the cathodes and planes. The black straight line show the detectors which have less than 5 tracks (poor statistics).

Comments

 For both MuTr and MuID, Millepede found the input misalignments within error bars.

Reco2: introducing corrections to align the data



MuTr and MuID

Plot description

- The top and bottom plots show w offsets in cm vs each detector (one point per half octant and panel). Middle plot is the number of tracks per detector.
- In blue are the input misalignments =
 input misalignments same as in reco1
 + corrections found by Millepede in
 reco1; in red the misalignments found
 by Millepede. The dashed lines
 separate the cathodes and planes. The
 black straight line show the detectors
 which have less than 5 tracks.

Comments

- Millepede corrected the detector alignment since every offset is now centered on 0 within error bars.
- The alignment is working on MC for MuTr + MuID.


Update

Simulations Reco1 Reco2

Real data

Reco1: aligning run3pp zerofield with survey Reco2

Reco1: founding misalignments



Plot description


- The top and bottom plots show w offsets in cm vs each detector (one point per half octant and panel). Middle plot is the number of tracks per detector.
- In blue are the input misalignments; in red the misalignments found by Millepede. The dashed lines separate the cathodes and planes. The black straight line show the detectors which have less than 5 tracks: the reconstructed dst have no clusters in plane 4, panel 0, 1, 2.

Comments

 The misalignments are especially seen in the last stations.

Reco2: introducing corrections

MuTr and MuID



Plot description

- The top and bottom plots show w offsets in cm vs each detector (one point per half octant and panel). Middle plot is the number of tracks per detector.
- In blue are the input misalignments = input misalignments same as in reco1 + corrections found by Millepede in reco1; in red the misalignments found by Millepede. The dashed lines separate the cathodes and planes. The black straight line show the detectors which have less than 5 tracks.

Comments

- Millepede corrected the detector alignment since every offset is now centered on 0 within error bars.
- The alignment is working on RD for MuTr + MuID.

Update

Simulations

Reco1

Reco2

Real data

Reco1: aligning run3pp zerofield with survey

Reco2

Conclusion

Conclusion

 The global alignment is working for the mutr and muid together without magnetic field.

To do

- Show the residuals in each panel for completeness.
- Look at a repass with the mutr muid alignment from Millepede → if the alignment is better and time allows, this file may be the one to commit in the DB.
- Write a technical note on the global alignment.